



seko

DOSING PUMPS

PS2 SERIES

PS2 SERIES - TECHNICAL SPECIFICATION

- » Capacity From 40 to 1000 L/h
- » Max Pressure 20 BAR
- » Stroke Rate 58 • 78 • 116 strokes/minute
- » Piston Diameter From 25 to 89 mm
- » Motor Standard 0,25 • 0,37 • 0,55 • 0,75 Kw (IP 55)
- » Stroke Length 25 mm

PRODUCT INFORMATION

Model	Piston Diamete	Strokes/min	Flow Rate (l/H)	Max Pressure				Connection		3 phases Motor (kw)
				BAR		PSI		SS 316	PVC	
				SS 316	PVC	SS 316	PVC			
PS2E025A PS2E025B PS2E025C	25	58 78 116	40 53 80	20	10	290	145	3/8 g f	3/8 g f	0,25
PS2E030A PS2E030B PS2E030C	30	58 78 116	55 75 112	20	10	290	145	3/8 g f	3/8 g f	0,25
PS2E038A PS2E038B PS2E038C	38	58 78 116	90 120 180	20	10	290	145	1/2 g f	3/8 g f	0,37
PS2E048A PS2E048B PS2E048C	48	58 78 116	140 190 284	20	10	290	145	1/2 g f	1/2 g f	0,55
PS2E054A PS2E054B PS2E054C	54	58 78 116	180 242 365	15	10	217,5	145	1/2 g f	1/2 g f	0,55
PS2E064A PS2E064B PS2E064C	64	58 78 116	250 335 505	10	10	145	145	3/4 g f	3/4 g f	0,75
PS2E076A PS2E076B PS2E076C	76	58 78 116	365 485 730	7	7	101,5	101,5	1 g f	1 g f	0,75
PS2E089A PS2E089B PS2E089C	89	58 78 116	495 660 1000	5	5	72,5	72,5	1 g f	1 g f	0,75

TOLL FREE:
1800 102 4466

www.aventura.co.in